

Mfg.	Disp.	Weight Oz.	Overall Length	Hole Spacing	Hole Width	Beam Inside	Beam Outside
Enya, 5224	29	8	2 5/8	9/16	1 21/32	1 1/4	1 61/64
Fox	15	4.5	2 1/16	1/2	1 1/8	15/16	1 1/2
Fox	15 X		2	1/2	1 1/8	15/16	1 1/2
Fox	15 C	5.5	2 1/4	1/2	1 3/8	1 1/16	1 11/16
Fox	19	6	2 1/4	9/16	1 7/16	1 1/16	1 3/4
Fox	25	5.5	2 1/4	9/16	1 7/16	1 1/16	1 3/4
Fox	35	6	2 1/4	9/16	1 7/16	1 3/16	1 3/4
Fox	35 X	8.5	2 11/16	5/8	1 9/16	1 1/4	1 15/16
Fox	40	9.5	2 3/4	1 1/4	1 11/16	1 5/16	2.0
Fox, ABC	35 S	6.5	2 1/4	9/16	1 7/16	1 3/16	1 3/4
Fox, CS	36 X		2 11/16	5/8	1 9/16	1 1/4	1 15/16
Fox, Rocket	35	7.5	2 7/16	5/8	1 1/2	1 1/4	1 13/16
Fox, Rocket	15	4	2	1/2	1 1/8	15/16	1 1/2
Jett, GMA	50 RE	10.26	3 11/64	1 11/16	1 25/32	1 13/16	2 1/64
Jett, GMA	50 SE	10.6	3 11/64	1 11/16	1 25/32	1 13/16	2 1/64
Johnson	35 SS	8	2 9/16	3/4	1 1/8	1 1/4	1 7/16
K & B	35	8.5	3 5/32	11/16	1 9/16	1 5/16	1 7/8
K & B	40	9.5	3 5/32	11/16	1 9/16	1 5/16	1 7/8
K&B	29 S	8.5	2 7/16	9/16	1 5/8	1 5/16	1 7/8
Magnum	36 XL	9	3 1/16	11/16	1 5/8	1 1/4	1 7/8
McCoy	40	8.5	2 1/2	5/8	1 9/16	1 5/16	1 7/8
McCoy	29	7.5	2 1/2	5/8	1 9/16	1 5/16	1 7/8
Merco	35	7.5	2 5/8	3/4	1 9/16	1 5/16	1 7/8
OS	20	5.25	2 7/16	9/16	1 1/2	1 1/8	1 3/4
OS	30 S	8	2 1/2	11/16	1 9/16	1 7/32	1 13/16
OS	35 S	8	2 1/2	11/16	1 9/16	1 7/32	1 13/16
OS, FP	40	8.5	2 15/16	11/16	1 9/16	1 1/4	1 7/8
OS, FP-S	35	8.5	2 15/16	11/16	1 9/16	1 1/4	1 7/8
OS Max	50	11	3 3/16	13/16	1 3/4	1 7/16	2 1/16
OS Max H	35 C	8.5	2 15/16	11/16	1 9/16	1 5/16	
OS Max H	40	8.5	2 15/16	11/16	1 9/16	1 5/16	
OS-F	25	7.25	3	9/16	1 1/2	1 3/16	1 13/16
OS-FP	20	7.25	2 7/16	9/16	1 1/2	1 1/8	1 3/4
OS-FP	25	6.5	2 7/16	9/16	1 1/2	1 1/8	1 3/4
ST G21	40	10	2 7/8	19/32	1 9/16	1 5/16	1 15/16
ST G21	46	10	2 7/8	19/32	1 9/16	1 5/16	1 15/16
ThndrTgr	36 Pro	8.5	3	9/16	1 1/2	1 1/4	1 3/4
Veco	19 BB	6.25	2 1/2	9/16	1 7/16	1 3/16	1 3/4
Veco	35	7.25	2 9/16	3/4	1 9/16	1 5/16	1 7/8
Veco	45 BB	12	2 15/16	1 1/16	1 13/16	1 7/16	2 1/8